

SECTION 1: Identification

1.1. Product identifier

Product form : Mixture
Product name : Transformation Siding & Trim Stain

1.2. Recommended use and restrictions on use

Recommended uses and restrictions : Coating (Wood Stain)

This SDS is designed for workplace employees, emergency personnel and for other situations where there is potential for large-scale or prolonged exposure, in accordance with the WHMIS GHS requirements.

This SDS is not applicable for consumer use of our products. For consumer use, all precautionary and first aid language is provided on the product label, SDS or both in accordance with applicable government regulations

1.3. Supplier

Supplier

Sashco Inc
10300 E. 107th Place
80601 Brighton, CO - USA
T 800 767 5656
info@sashco.com

Distributor

Add the name, address and tel. number of the Canadian manufacturer or importer who operates in Canada

1.4. Emergency telephone number

Emergency number : 800 535 5053

SECTION 2: Hazard identification

2.1. Classification of the substance or mixture

Classification (GHS-CA)

Skin Sens. 1 H317

2.2. GHS Label elements, including precautionary statements

GHS-CA labelling

Hazard pictograms (GHS-CA) :



Signal word (GHS-CA) : Warning

Hazard statements (GHS-CA) : H317 - May cause an allergic skin reaction

Precautionary statements (GHS-CA) :

- P261 - Avoid breathing dust/fume/gas/mist/vapours/spray
- P272 - Contaminated work clothing should not be allowed out of the workplace
- P280 - Wear protective gloves/protective clothing/eye protection/face protection
- P302+P352 - IF ON SKIN: Wash with plenty of water
- P362+P364 - Take off contaminated clothing and wash it before reuse
- P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
- P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS-CA)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Naphtha, petroleum, hydrotreated heavy	(CAS-No.) 64742-48-9	3.40
5-Decyne-4,7-diol, 2,4,7,9-tetramethyl-	(CAS-No.) 126-86-3	1.35
3-Iodo-2-propynyl butylcarbamate	(CAS-No.) 55406-53-6	0.35

Transformation Siding & Trim Stain

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures after inhalation : If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
- First-aid measures after skin contact : IF ON SKIN: Wash with plenty of Water. Take off contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
- First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
- First-aid measures after ingestion : Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
- Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.
- Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
- Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Immediate medical attention and special treatment, if necessary

- Other medical advice or treatment : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

- Suitable extinguishing media : Water fog. Carbon dioxide. Dry chemical. Foam.

5.2. Unsuitable extinguishing media

- Unsuitable extinguishing media : None known.

5.3. Specific hazards arising from the hazardous product

- Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Oxides of nitrogen.

5.4. Special protective equipment and precautions for fire-fighters

- Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
- Reactivity : Material will oxidize and can cause SPONTANEOUS COMBUSTION of contaminated rags, sawdust, or other ignitable absorbent material. Immerse in water immediately.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Contaminated rags or other ignitable absorbent material used in clean up should be laid flat to dry completely before disposal or immersed in water immediately to prevent spontaneous combustion.

6.2. Methods and materials for containment and cleaning up

- For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
- Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

6.3. Reference to other sections

- For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke.
- Hygiene measures : Wash contaminated clothing before reuse. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Keep out of the reach of children. Keep container tightly closed. Keep from freezing.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

- No additional information available

Transformation Siding & Trim Stain

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves resistant to chemical penetration

Eye protection:

Safety glasses or goggles are recommended when using product.

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Coloured liquid
Colour	: Brown
Odour	: Mild amine
Odour threshold	: No data available
pH	: 8.5 - 9
Relative evaporation rate (butylacetate=1)	: No data available
Relative evaporation rate (ether=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: $\approx 212\text{ }^{\circ}\text{C}$ / $100\text{ }^{\circ}\text{C}$
Flash point	: $> 200\text{ }^{\circ}\text{F}$ / $93.3\text{ }^{\circ}\text{C}$
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Vapour pressure at 50 °C	: No data available
Relative density	: 1.03
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Viscosity, kinematic	: 75 cSt
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	: No dangerous reactions known under normal conditions of use.
Chemical stability	: Stable under normal conditions.
Possibility of hazardous reactions	: No dangerous reactions known under normal conditions of use.
Conditions to avoid	: Heat. Incompatible materials.
Incompatible materials	: Strong oxidizing agents.
Hazardous decomposition products	: May include, and are not limited to: oxides of carbon. Oxides of nitrogen.

Transformation Siding & Trim Stain

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

Naphtha, petroleum, hydrotreated heavy (64742-48-9)

LD50 oral rat	> 6000 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat	> 8500 mg/m ³ (Exposure time: 4 h)

5-Decyne-4,7-diol, 2,4,7,9-tetramethyl- (126-86-3)

LD50 oral rat	> 500 mg/kg
LD50 dermal rabbit	> 1000 mg/kg
LC50 inhalation rat	> 20 mg/l (Exposure time: 1 h)

3-Iodo-2-propynyl butylcarbamate (55406-53-6)

LD50 oral rat	1470 mg/kg
LD50 dermal rabbit	> 2000 mg/kg

Skin corrosion/irritation : Not classified.
pH: 8.5 - 9
Serious eye damage/irritation : Not classified.
pH: 8.5 - 9
Respiratory or skin sensitization : May cause an allergic skin reaction.
Germ cell mutagenicity : Not classified.
Carcinogenicity : Not classified.
Reproductive toxicity : Not classified.
STOT-single exposure : Not classified.
STOT-repeated exposure : Not classified.
Aspiration hazard : Not classified.

Transformation Siding & Trim Stain

Viscosity, kinematic (40 °C)	75 mm ² /s
------------------------------	-----------------------

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
Symptoms/effects after skin contact : May cause skin irritation. Repeated exposure may cause skin dryness or cracking. May cause an allergic skin reaction.
Symptoms/effects after eye contact : May cause eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : May cause long-term adverse effects in the aquatic environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. The generation of waste should be avoided or minimized wherever possible.

Transformation Siding & Trim Stain

Safety Data Sheet

according to the Hazardous Products Regulation (February 11, 2015)

SECTION 14: Transport information

14.1. Basic shipping description

In accordance with TDG

Transportation of Dangerous Goods

Not regulated for transport

14.2. Transport information/DOT

No additional information available

14.3. Air and sea transport

IMDG

Not regulated for transport

IATA

Not regulated for transport

SECTION 15: Regulatory information

15.1. National regulations

No additional information available

15.2. International regulations

No additional information available

SECTION 16: Other information

Date of issue : 09/25/2017

Revision date : 01/22/2018

Other information : None.


Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.

NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity : 1 - Materials that in themselves are normally stable but can become unstable at elevated temperatures and pressures.



Hazard Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Personal protection : B - Safety glasses, Gloves

SDS Canada (GHS)_NEXREG_NEW

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.