



Deck & Fence Formula

Technical Data Sheet

March 2013

TR-Series

Description

Timber Pro Deck & Fence Natural Oil Wood finish is a premium exterior wood finish formulated with a unique blend of natural oils and resins. Deck & Fence Formula utilizes a unique formula which gives ultimate penetration into the wood. Deck and Fence formula not only accentuates the natural beauty of the wood but it also provides u protection against the damaging UV rays from the sun and destructive effects of the elements.

Where to Use

Timber Pro Deck and Fence Formula can be used on all new and reconditioned exterior wood. The Deck and Fence formula can be used on all wood species such as cedar, fir , pine ,cypress, redwood, spruce and pressure treated wood. The following are areas of use for the Deck and Fence Formula.

- Decks
- Fences

RESTRICTIONS

- Do not thin
- Do not apply over previously coated surfaces

Features and Benefits

- Low V.O.C.
- Excellent UV protection
- Excellent weathering properties
- Large color range
- Easy soap and water cleanup



Deck & Fence Formula

Technical Data Sheet
March 2013

TR-Series

Color Range and Packaging

Color :

(TR series) Transparent

25 colors available

Packaging: 1 US Gallon
5 US gallon Pail

Properties

Viscosity -	20-23 secs Zahn cup #2
Gloss Level -	Satin 25-35 GU @ 60 degree
Solids by Weight -	17.8 % +/- 1%
Solids by Volume -	18.1% +/- 1%
V.O.C. -	92 g/l minus water
Weight per gallon-	8.49 lbs./Gal.
Specific Gravity-	1.02
Dry Time -	2-4 touch dry 16 hours through dry for heavy traffic Note dry times will be extended at low temperatures and high humidity

Shelf Life

Approximately two years in an unopened container

KEEP FROM FREEZING

Coverage

Smooth Wood: 300-400 square feet per gallon

Rough Wood : 150 – 200 square feet per gallon

Hardwoods: 400-450 square feet per gallon

Note : Coverage will vary with the porosity of the wood



Deck & Fence Formula

Technical Data Sheet

TR-Series

March 2013

Application

Use a spray applicator , nylon polyester brush or paint pad

Clean Up

With soap and mild detergent

Product Disclaimer

The technical information and suggestions for use herein are based on Timber Pro Coatings Ltd research and experience and believed to be reliable. But such information and suggestions do not constitute a warranty. Since Timber Pro Coatings has no control over the conditions under which the product is transported, stored, handled, used or applied, buyers must determine for themselves by preliminary tests or otherwise the suitability of the product for their purposes.

Timber Pro Coatings Ltd

#140-12051 Horseshoe Way, Richmond, BC V7A 4V4
Ph: 604-270-4244 Fax: 604-270-4247 Toll Free: 1-877-666-4244
Email: canadainfo@timberprocoatings.com