

SAFETY DATA SHEET

SECTION 1: IDENTIFICATION

Product identifier used on the label: Product Name: LIFE

LIFELINE Wood Renew

Other means of identification:

Recommended use of the chemical and restrictions on use:

Chemical manufacturer address and telephone number:		
Manufacturer Name:	Perma-Chink Systems, Inc.	
Address:	1605 Prosser Road Knoxville, TN 37914 USA	
Website:	www.permachink.com	
General Phone Number:	800-548-3554	
General Fax Number:	865-523-9475	
Customer Service Phone Number:	865-524-7343	
General Phone Number: General Fax Number:	USA www.permachink.com 800-548-3554 865-523-9475	

Emergency phone number: Emergency Phone Number:

CHEMTREC 1-800-424-9300

SECTION 2: HAZARD(S) IDENTIFICATION

Classification of the chemical in accordance with CFR 1910.1200(d)(f):

GHS Pictograms:	
Signal Word:	DANGER.
GHS Class:	Serious Eye Damage. category 1. Skin corrosion. category 1. Acute Oral Toxicity. Category 4. Specific Target Organ Toxicity - STOT, Single Exposure SE. Category 3 (RESP. IRR.).
Hazard Statements:	H318 - Causes serious eye damage. H314 - Causes severe skin burns and eye damage. H302 - Harmful if swallowed. H335 - May cause respiratory irritation.
Precautionary Statements:	 P260 - Do not breathe dust/fume/gas/mist/vapours/spray. P261 - Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash hands thoroughly after handling. P270 - Do not eat, drink or smoke when using this product. P271 - Use only outdoors or in a well-ventilated area. P280 - Wear protective gloves/protective clothing/eye protection/face protection. P301+P312 - IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do not induce vomiting. P303+P361+P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. P304+P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor/physician. P312 - Call a POISON CENTER or doctor/physician. P312 - Call a POISON CENTER or doctor/physician. P313 - Specific treatment (see on this label). P330 - Rinse mouth. P330 - Rinse mouth. P330 - Rinse mouth. P330 - Store in a well-ventilated place. Keep container tightly closed. P403+P233 - Store in a well-ventilated place. with Local, State, Federal and Provincial regulations.

Hazards not otherwise classified that have been identified during the classification process:

Potential Health Effects:	
Eye:	Corrosive. Will cause eye burns and permanent tissue damage.
Skin:	Severely irritating; may cause permanent skin damage.
Inhalation:	May cause severe respiratory system irritation.
Ingestion:	Harmful if swallowed. Corrosive to the gastrointestinal tract.
Chronic Health Effects:	Prolonged skin contact causes burns. Repeated or prolonged inhalation may cause toxic effects.
Signs/Symptoms:	Depending on solution concentration, material may be corrosive to skin, mucous membranes and eyes. Vapors may cause respiratory irritation.
Target Organs:	Eyes. Skin. Respiratory system. Digestive system.
Aggravation of Pre-Existing Conditions:	May aggravate pre-existing respiratory disorders, allergy, eczema, or skin conditions.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

	TU		

Chemical Name	CA S#	Ingredient Percent	EC Num.
Sodium Carbonate Peroxyhydrate	15630-89-4	65- 75 by weight	239-707-6
Non-hazardous		23 - 33 by weight	

SECTION 4: FIRST AID MEASURES

Description of necessary m	easures:
Eye Contact:	Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing. Get medical attention, if irritation or symptoms of overexposure persists.
Skin Contact:	Immediately wash skin with plenty of soap and water for 15 to 20 minutes, while removing contaminated clothing and shoes. Get medical attention if irritation develops or persists.
Inhalation:	If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.
Ingestion:	If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

SECTION 5: FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media:

ION 5: FIRE FIGHTING MEASURES	

Protective Equipment:	As in any fire, and full protec	wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent) ctive gear.
NFPA Ratings:		
NFPA Health:	3	
NFPA Flammability:	1	3 2
NFPA Reactivity:	2	

Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires involving this material.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective ec	uipment and emergency procedures:
Personal Precautions:	Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use proper personal protective equipment as listed in Section 8.
Environmental precautions:	
Environmental Precautions:	Avoid runoff into storm sewers, ditches, and waterways.
Methods and materials for contain	ment and cleaning up:
Methods for containment:	Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by covering, diking or other means. Provide ventilation.
Methods for cleanup:	Clean up spills immediately observing precautions in the protective equipment section. Provide ventilation.

Precautions for safe handli	ng:
Handling:	Corrosive. Use proper personal protective equipment as listed in section 8. Use with adequate ventilation. Avoid breathing vapor and contact with eyes, skin and clothing. Wash hands thoroughly after handling.
Hygiene Practices:	Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.
Conditions for safe storage	, including any incompatibilities:
Storage:	Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and incompatible substances. Keep container tightly closed when not in use. Keep only in the original, corrosive resistant container and store locked up.

SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

EXPOSURE GUIDELINES:	
Appropriate engineering controls:	
Engineering Controls:	Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.
Individual protection measures:	
Eye/Face Protection:	Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulation, or the European standard EN 166.
Skin Protection Description:	Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.
Respiratory Protection:	A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.
Other Protective:	Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.
PPE Pictograms:	

SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

PHYSICAL AND CHEMICAL PROPERT	IES:
Physical State:	Solid
Physical State Appearance:	Solid.
Color:	White
Odor:	None.
Odor Threshold:	No Data
Boiling Point:	Not applicable.
Melting Point:	No Data
Density:	9.5 - 10.0 lb./gal
Specific Gravity:	1.14 - 1.19
Solubility:	< 150 g/L
Vapor Density:	Not applicable.
Vapor Pressure:	Not applicable.
Evaporation Rate:	Not applicable.
pH:	Not applicable.
Molecular Formula:	Mixture
Viscosity:	Not applicable.
Coefficient of Water/Oil Distribution:	Not applicable.
Flammability:	No Data
Flash Point:	No Data
Lower Flammable/Explosive Limit:	Not applicable.
Upper Flammable/Explosive Limit:	Not applicable.
Oxidizing Properties:	Oxidizer, Oxidizing Agent
VOC Content:	No Data

SECTION 10: STABILITY and REACTIVITY Chemical Stability:

Chemical Stability:	Stable under normal temperatures and pressures.
Possibility of hazardous reactions:	
Hazardous Polymerization:	Not reported.
Conditions To Avoid:	
Conditions to Avoid:	Heat, flames, incompatible materials, freezing or temperatures below 32 deg. F.
Incompatible Materials:	
Incompatible Materials:	Oxidizing agents. Strong acids and alkalis.

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION:

Sodium Carbonate Peroxyhydrate:

Ingestion:

Oral - Rat LD50 - Lethal dose, 50 percent kill: 2400 mg/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Dyspnea] Oral - Rat LD50 - Lethal dose, 50 percent kill: 2400 mg/kg [Behavioral - Somnolence (general depressed activity) Behavioral - Ataxia Lungs, Thorax, or Respiration - Respiratory depression] Oral - Rat LD50 - Lethal dose, 50 percent kill: 2400 mg/kg [Behavioral - Somnolence (general depressed activity) Lungs, Thorax, or Respiration - Respiratory depression] (RTECS)

SECTION 12	2 FCOL	OGICAL	INFORMATION

Ecotoxicity:	
Ecotoxicity:	Toxic to aquatic life with long lasting effects.
Environmental Fate:	No information available.

SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste:

Waste Disposal:

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classifications of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and/or state and local guidelines.

SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name:	Paint Related Material.
DOT UN Number:	UN3066
DOT Hazard Class:	8
DOT Packing Group:	П
DOT Exemption:	Not applicable.
IATA Shipping Name:	Paint Related Material.
IATA UN Number:	3066
IATA Hazard Class:	8
IATA Packing Group:	II
Canadian Shipping Name:	Paint Related Material.
Canadian UN Number:	3066
Canadian Hazard Class:	8
Canadian Packing Group:	II
IMDG UN Number:	3066
IMDG Shipping Name:	Paint Related Material.
IMDG Hazard Class:	8
IMDG Packing Group:	П
ADR UN Number:	3066
ADR Shipping Name:	Paint Related Material.
ADR Hazard Class:	8
ADR Packing Group:	II

SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

Sodium Carbonate Peroxyhyd	rate:	
TSCA Inventory Status:	Listed	
Canada DSL:	Listed	
EC Number:	239-707-6	

SECTION 16: ADDITIONAL INFORMATION

HMIS Ratings:		Health Hazard	3
HMIS Health Hazard:	3	Fire Hazard	1
HMIS Fire Hazard:	1	Reactivity	2
HMIS Reactivity:	2	Personal Protection	х
HMIS Personal Protection:	х		
SDS Creation Date:	July 30, 2015		
SDS Revision Date:	August 23, 2022		
SDS Format:			
SDS Author:	Perma-Chink Systems, Inc.		
Disclaimer:	The information contained herein is, to the best of Perma-Chink Sys of the date indicated. Since the information contained herein may b our control and with which we may be unfamiliar, and since data ma date hereof may suggest modifications of the information, we do no results of its use. This information is furnished on the condition that their own determination as to the suitability of the material for their condition that they assume the risk of use thereof.	e applied under conditions be de available subsequent to th ot assume responsibility for th t the person receiving it shall	yond e e make