

## **SAFETY DATA SHEET**

### SECTION 1: IDENTIFICATION

Product identifier used on the label:

Product Name: Prelude

Other means of identification:

Recommended use of the chemical and restrictions on use:

<u>Chemical manufacturer address and telephone number:</u>

Manufacturer Name: Perma-Chink Systems, Inc.

Address: 1605 Prosser Road Knoxville, TN 37914

USA

Website: www.permachink.com
General Phone Number: 800-548-3554
General Fax Number: 865-523-9475
Customer Service Phone Number: 865-524-7343

Emergency phone number:

Emergency Phone Number: CHEMTREC 1-800-424-9300

## SECTION 2: HAZARD(S) IDENTIFICATION

 $\underline{Classification\ of\ the\ chemical\ in\ accordance\ with\ CFR\ 1910.1200(d)(f):}$ 

Signal Word: Not applicable.

GHS Class: Not classified as hazardous according to OSHA Hazard Communication Standard, 29 CFR 1910.1200..

Hazard Statements: Not applicable.

Precautionary Statements: Not applicable.

Hazards not otherwise classified that have been identified during the classification process:

Potential Health Effects:

Eye: May causes eye irritation.

Skin: May causes skin irritation.

Inhalation: Prolong or excessive inhalation may cause respiratory tract irritation.

Ingestion: May be harmful if swallowed. May cause vomiting.

Chronic Health Effects: Prolong or repeated contact may cause sin irritation.

Signs/Sympthoms: Over exposure may cause headaches and dizziness.

Target Organs: Eyes, skin, respiratory system and digestive system.

Aggravation of Pre-Existing Conditions: None generally recognized.

### SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

# Mixtures:

Chemical Name	CAS#	Ingredient Percent	EC Num.
.Proprietary Polymer		15 - 25 by weight	
Non-hazardous		70 - 80 by weight	
Synthetic Amorphous, Pyrogenic silica	7631-86-9	0.5 - 1.0 by weight	262-373-8
Propylene glycol	57-55-6	2 - 3 by weight	200-338-0
2,2,4-trimethyl-1,3-pentanediol monoisobutyrate	25265-77-4	0.5 - 1.5 by weight	246-771-9

Prelude
Revision: 9/1/2022

## SECTION 4: FIRST AID MEASURES

Description of necessary measures:

Eye Contact: Immediately flush eyes with plenty of water for at least 15 to 20 minutes. Ensure adequate flushing of

the eyes by separating the eyelids with fingers. Remove contacts if present and easy to do. Continue rinsing. Get medical attention, if irritation or symptoms of overexposure persists.

Skin Contact: Immediately wash skin with soap and plenty of water.

Get medical attention if irritation develops or persists.

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained

personnel. Seek immediate medical attention.

If swallowed, do NOT induce vomiting. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Inaestion:

## SECTION 5: FIRE FIGHTING MEASURES

Suitable and unsuitable extinguishing media:

Suitable Extinguishing Media: Use alcohol resistant foam, carbon dioxide, dry chemical, or water fog or spray when fighting fires

involving this material.

Special protective equipment and precautions for fire-fighters:

Protective Equipment: As in any fire, wear Self-Contained Breathing Apparatus (SCBA), MSHA/NIOSH (approved or equivalent)

and full protective gear.

**NFPA Ratings:** 

NFPA Health: 1 NFPA Flammability: 1 NFPA Reactivity: 0



### SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Personal Precautions:  $\hbox{\bf Evacuate area and keep unnecessary and unprotected personnel from entering the spill area. Use } \\$ 

proper personal protective equipment as listed in Section 8.

Environmental precautions:

Environmental Precautions: Avoid runoff into storm sewers, ditches, and waterways.

Methods and materials for containment and cleaning up:

Methods for containment: Contain spills with an inert absorbent material such as soil or sand. Prevent from spreading by covering, diking or other means. Provide ventilation.

Clean up spills immediately observing precautions in the protective equipment section. Place into a suitable container for disposal. Provide ventilation. After removal, flush spill area with soap and water Methods for cleanup:

to remove trace residue.

## SECTION 7: HANDLING and STORAGE

Precautions for safe handling:

Use with adequate ventilation. Avoid breathing vapors and contact with eyes, skin and clothing. Handling:

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

Conditions for safe storage, including any incompatibilities:

Store in a cool, dry, well ventilated area away from sources of heat, combustible materials, and Storage:

incompatible substances. Keep container tightly closed when not in use.

Prelude Perma-Chink Systems, Inc. Revision: 9/1/2022 Page 2 of 6

## SECTION 8: EXPOSURE CONTROLS, PERSONAL PROTECTION

# EXPOSURE GUIDELINES:

#### Appropriate engineering controls:

Engineering Controls:

Use appropriate engineering control such as process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

#### Individual protection measures:

Eye/Face Protection:

Wear appropriate protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye

and face protection regulation, or the European standard EN 166.

Skin Protection Description:

Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eyes, skin or clothing.

Respiratory Protection:

A NIOSH approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection.

Other Protective:

Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety

shower.

#### PPE Pictograms:





### SECTION 9: PHYSICAL and CHEMICAL PROPERTIES

#### PHYSICAL AND CHEMICAL PROPERTIES:

Physical State: Liauid. Color: Off White

Odor: Slight latex odor

**Boiling Point:** 212°F Melting Point: No Data

8.40 - 8.65 lb./gal Density:

1.02 - 1.04 Specific Gravity: Specific Volume: No Data Solubility: No Data Vapor Density: No Data Vapor Pressure: No Data

Percent Volatile: 79 - 82 **Evaporation Rate:** No Data **Evaporation Point:** No Data pH: 8.0 - 8.5Molecular Formula: Mixture

Molecular Weight: Not applicable. Viscosity: 250 - 300 cP

Coefficient of Water/Oil Distribution:

No Data

Flammability: No Data Flash Point: No Data

Lower Flammable/Explosive Limit: Not applicable. Upper Flammable/Explosive Limit: Not applicable.

**Explosive Properties:** No Data Oxidizing Properties: No Data Refractive Index: No Data Optical Rotation: No Data

VOC Content: < 200 g/L (Less Water)

Prelude Revision: 9/1/2022

### SECTION 10: STABILITY and REACTIVITY

**Chemical Stability:** 

Chemical Stability: Stable under normal temperatures and pressures.

Possibility of hazardous reactions:

Hazardous Polymerization: Not reported.

Conditions To Avoid:

Conditions to Avoid: Heat, flames, incompatible materials, and freezing or temperatures below 32 deg. F.

**Incompatible Materials:** 

Incompatible Materials: Oxidizing agents. Strong acids and alkalis.

## SECTION 11: TOXICOLOGICAL INFORMATION

### TOXICOLOGICAL INFORMATION:

### Synthetic a morphous, pyrogenic silica:

Administration into the eye - Rabbit Standard Draize test: 25 mg/24H [Mild] (RTECS) Eve:

Propylene glycol:

Eye:

Administration into the eye - Rabbit Standard Draize test: 100 mg [Mild]
Administration into the eye - Rabbit Standard Draize test: 500 mg/24H [Mild] (RTECS)

Skin: Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 20800 mg/kg [Details of

Administration onto the skin - Rabbit LD50 - Lethal dose, 50 percent kill: 20000 mg/kg [Behavioral - Ataxia Behavioral - Tetany Lungs, Thorax, or Respiration - Respiratory depression] (RTECS)

Ingestion: Oral - Rat LD50 - Lethal dose, 50 percent kill: 20 gm/kg [Details of toxic effects not reported other

than lethal dose value] (RTECS)

### 2,2,4-trimethyl-1,3-pentanediolmonoisobutyrate:

Rabbit - LD50 6300 uL/kg.

Ingestion: Rat - LD50 2000 mg/kg

## SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity:

Ecotoxicity: Do not empty into drains or waterways.

Environmental Fate: No data available.

## SECTION 13: DISPOSAL CONSIDERATIONS

Description of waste:

Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classification of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines to ensure compliance. Waste Disposal:

Prelude Perma-Chink Systems,Inc. Revision: 9/1/2022 Page 4 of 5

## SECTION 14: TRANSPORT INFORMATION

DOT Shipping Name: Not restricted as a dangerous good.

DOT UN Number: Not restricted as a dangerous good.

IATA Shipping Name: Not restricted as a dangerous good.

IATA UN Number: Not restricted as a dangerous good.

Canadian Shipping Name: Not restricted as a dangerous good.

Canadian UN Number: Not restricted as a dangerous good.

IMDG UN Number: Not restricted as a dangerous good.

IMDG Shipping Name: Not restricted as a dangerous good.

ADR UN Number: Not restricted as a dangerous good.

ADR Shipping Name: Not restricted as a dangerous good.

## SECTION 15: REGULATORY INFORMATION

Safety, health and environmental regulations specific for the product:

#### Amorphous silicon dioxide, chemically prepared:

TSCA Inventory Status: Listed Canada DSL: Listed 262-373-8 FC Number:

Propylene glycol:

TSCA Inventory Status: Listed Canada DSL: Listed EC Number: 200-338-0

### $\underline{\textbf{2,2,4-trimethyl-1,3-pentanediolmonoisobutyrate}}:$

TSCA Inventory Status: Listed Canada DSL: Listed EC Number: 246-771-9

### SECTION 16: ADDITIONAL INFORMATION

# **HMIS Ratings:**

HMIS Health Hazard: HMIS Fire Hazard: 1 HMIS Reactivity: HMIS Personal Protection:

Health Hazard	1
Fire Hazard	1
Reactivity	0
Personal Protection	х

SDS Creation Date: July 30, 2015 SDS Revision Date: September 1, 2022

SDS Format:

SDS Author: Perma-Chink Systems, Inc.

Disclaimer:

The information contained herein is, to the best of Perma-Chink Systems, Inc. knowledge, accurate as of the date indicated. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume responsibility for the results of its use. This information is furnished on the condition that the person receiving it shall make their own determination as to the suitability of the material for their particular purpose and on the condition that they assume the risk of use thereof.

Prelude Perma-Chink Systems, Inc. Revision: 9/1/2022 Page 5 of 5